



Hose & Supply Boxes 8120 Series

Hose Valves



8120

8135-CP

Fixture May Show Some Available Options

Please visit www.acorneng.com for most current specifications.

Hose Valves

Acorn Hose Valves are recommended for installation in interior and exterior locations not subject to freezing. Hose valves have heavy rough brass body with machined brass vandal-resistant lock shield bonnet and are furnished with a removable wheel handle. Valves close with the pressure and feature a replaceable cartridge which contains all wearing parts including the seat. Inlet is 3/4" NPT female. Outlet is 3/4" male hose thread. Vacuum breaker models prevent contamination of potable water supply. Vacuum breakers are atmospheric type and conform to the requirements of ASSE Standard 1011. Check local code authority for vacuum breaker requirements.

Installation. 8120 and 8121 models have flanges and are used for installation on walls of buildings. 8125, 8126, 8130 and 8131 models are normally installed on supply pipes 6" to 36" high. 8135 and 8136 models are installed flush with surface in planter boxes, etc.

GUIDE SPECIFICATION

Provide and install Acorn Hose Valves model (specify model number) cartridge-operated hose valve with lock shield bonnet and removable key handle. Interior wall hose valves shall be polished chrome finish. Exterior valves shall be rough chrome-plated.



Hose & Supply Boxes 8120: Hose Valves

BASE MODEL NUMBER (Must Specify)

Product Options

- CP Chrome-Plated Polished
- CR Chrome-Plated Rough

HOSE VALVE

BENT NOSE WITH FLANGE

- 8120 Less Vacuum Breaker
- 8121 With Vacuum Breaker

BENT NOSE

- 8125 Less Vacuum Breaker
- 8126 With Vacuum Breaker


STRAIGHT NOSE

- 8130 Less Vacuum Breaker
- 8131 With Vacuum Breaker


INVERTED NOSE

- 8135 Less Vacuum Breaker
- 8136 With Vacuum Breaker


Please visit www.acorneng.com for most current specifications.




MODELS: 8120




8121




8125




8126




MODELS: 8130



8131



8135



8136

NOTES:

- 1. Wheel Handle (removable).
- 2. Hose Connection.
- 3. Vacuum Breaker.

<p>Important: Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acorn assumes no responsibility for use of void or superseded data. © Copyright 2008 Acorn Engineering Company</p>	
<p style="text-align: center;">Selection Summary</p> <p>Model No. & Option _____</p> <p>Quantity _____</p>	<p style="text-align: center;">Approved for Manufacturing</p> <p>Company _____ Title _____</p> <p>Signature _____ Date _____</p>