



## Penal-Ware® 1400 Series Modular Service Center



1426-LO-2-LVM-MSM1-PH

Fixture May Show Some Available Options

Please visit [www.acorneng.com](http://www.acorneng.com) for most current specifications.

### Modular Service Center

Fixture consists of three modules on a single Wall Sleeve: a Lighting/Ventilation Module, a Mirror/Shelf Module, and a Lav/Toilet Module. Modules are arranged for installation on finished wall and serviced from an accessible pipe chase. Fixture is fabricated from 14 gage, type 304 stainless steel and exposed surfaces have a satin finish.

**Lighting/Ventilation Modules.** A tamper-resistant task light and night light are provided. Lights are remotely controlled from a central control. Lenses are of tempered glass and clear acrylic protected by a stainless steel grid. Ventilation Grille is 1/4" square-punched holes providing 20 sq. inches of free area. Factory-installed plenum is ducted to the chase wall and vented to the left, right, or both sides. See Supplementary Sheet for details.

**Mirror/Shelf Module.** Mirror is highly polished, type 400 series stainless steel reinforced by galvanized steel backing plate. Mirror is serviceable from chase. Recessed shelf is provided for toiletries, books, etc. See Supplementary Sheet for details.

**Lav/Toilet Module.** Refer to 1426 Series, Lav/Toilet Comby sheet for details.

Optional Wall Sleeve is a single unit providing for an easy and accurate installation. All ventilation, electrical, plumbing, and mounting connections are made in one wall penetration. Wall Sleeve accurately locates each module and provides a security reinforcing channel at inter-modular joints.

#### GUIDE SPECIFICATION

Provide and install Acorn Modular Service Center consisting of Lighting/Ventilation Module, Mirror/Shelf Module, and Lav-Toilet Module, prewired and preplumbed to the chase wall. Service Center shall be of tamper-resistant construction secured from the chase. Service Center shall measure 26" wide x 30" deep (including toilet) x 95" high, with each module individually mounted onto one Wall Sleeve. Wall Sleeve shall be 18 gage, galvanized steel one-piece welded construction, shall accurately locate and mount all modules, and shall provide a security reinforcing channel at inter-modular joints. Mirror shall be type 400 stainless steel polished to a mirror finish 10-3/4" wide x 30-3/4" high. Mirror shall be provided with galvanized steel backing plate and shall be serviceable from chase side. Recessed shelf shall be 7-3/4" wide x 12" high x 6" deep. Toilet shall be blowout jet type with elongated bowl, and have integral flushing rim with highly polished integral seat. Cabinet shall have integral air return vent.

