

Penal-Ware[®] 1630 Series

Stainless Steel Mop Sink



Please visit www.acorneng.com for most current specifications.

Mop Sink

Fixture is fabricated of 16 gage, type 304 stainless steel and is seamless welded construction with satin finish on exposed exterior surfaces. Unit is arranged to be installed onto a floor and against finished wall.

Mop Sinks are 8" deep with an integral basin and is sound deadened with a fire resistant material. Integral drain includes a removable flat grid strainer and provides for an inside gasket connection to 3" IPS pipe. The mop sink is pitched to the drain outlet to provide positive drainage and includes an apron on three sides.

Optional Tiling Flanges extend 1" above the shoulder and can be specified for up to 3 sides. When the -TF Tiling Flange option is specified, an apron will not be provided on the specified sides.

Accessories to complete the installation of the mop sink include:

- Chrome Finish Faucet
- 36" Hose -To reduce splashing. Includes hose wall hanger
- Mop Hanger Provides easy storage of the mop over the sink
- Rubber drain gasket Eases drain connection
- Stainless Steel Wall Guards Protects sensitive walls from splashing water
- Tiling Flanges Simplifies field installation.
- A beehive dome strainer is optionally available.

GUIDE SPECIFICATION

Provide and install Acorn Penal-Ware Stainless Steel Mop Sink (specify model number and options). Fixture shall be fabricated of 16 gage, type 304 stainless steel. Unit shall be of seamless welded construction with all welds ground smooth. All exposed surfaces shall have a satin finish. Basin shall be double wall construction with aprons on three sides and shall provide a inside gasket waste connection to 3" IPS pipe and include a removable grid strainer.

Page 1 P.1630 Revised: 08/06/18

Penal-Ware®: 1630 Stainless Steel Mop Sink

MODEL AND OPTIONS SELECTION:

| BASE | MODEL | NUMBER | (Must | Specify) |
|------|-------|--------|-------|----------|
| | | | | |

| 🗋 1630 | Mop Sink, | 24" x | 24" | х | 10″ | Deep |
|--------|-----------|-------|-----|---|-----|------|
| 🔲 1636 | Mop Sink, | 36" x | 24″ | х | 10″ | Deep |
| | | | | | | |

INTEGRAL TILING FLANGES

| 🛄 -TF1 | Tiling Flange, Rear Side |
|--------|-----------------------------------|
| 🗋 -TF2 | Tiling Flange, Two Adjacent Sides |
| | 🔲 Rear & Right Side |
| | 🔲 Rear & Left Side |
| 🗋 -TF3 | Tiling Flange, Three Sides |
| | (Rear, Right and Left Sides) |

| PRODUCT | OPTIONS (Must Specify) |
|----------|---------------------------------------|
| 🗋 -BDS | Beehive Dome Strainer |
| 🔲 -KDG3 | Rubber Drain Gasket for 3" Waste Pipe |
| 🗋 -KFC | Chrome Utility Faucet, Hot & Cold, |
| | 8" Centerset (not Vandal Resistant; |
| | Shipped Loose) |
| 🗋 -KH36 | 36" Long Hose with Wall Hanger |
| 🔲 -КМН | 3 Mop Hanger Stainless Steel Bracket |
| 🔲 -KWG24 | Stainless Steel Wall Guard, 12" x 24" |
| | Specify Quantity: |
| | (Shipped Loose) |
| 🗋 -KWG36 | Stainless Steel Wall Guard, 12" x 36" |
| | Specify Quantity: |
| | (Shipped Loose) |
| 🔲 -ТА | Threshold Anchors |
| | |

a alfur)

Please visit <u>www.acorneng.com</u> for most current specifications.



Acorn Engineering Company • 15125 Proctor Avenue • P.O. Box 3527 • City of Industry, CA 91744-0527 U.S.A. Tel: (800) 488-8999 • (626) 336-4561 • Fax: (626) 961-2200 • www.acorneng.com • E-mail: info@acorneng.com

