



Please visit **www.acorneng.com** for most current specifications.

Zenith Built-In Wall Showers - ADA/CBC (Calif. Title 24) Compliant

Shower is designed to be installed on a finished wall from the front and includes as standard equipment: Control Valve, Flanged Fixed Upper Showerhead, Handheld Shower and Hose, Diverter Valve, Recessed Soap Dish, two-wall stainless steel Grab Bar and 1103 series Padded Vinyl Folding Seat. When installed properly and in accordance with all Shower Stall Type requirements, unit will conform with 2010 ADA Standards and CBC (California Title 24) 2019 Access Compliance Reference Manual with DSA Access Compliance Code Cycle Supplement effective July 1, 2021. Controls should be located on wall in accordance with shower stall type and configuration. Refer to applicable Accessibility Guidelines for complete details.

Compliance is subject to the interpretation and requirements of the local code authority.

Riser piping between Valve and Showerhead is furnished by others. Valve Supply Inlets and Showerhead include 1/2" NCT socket connections. Air-Control valves and Showerhead combinations include push-in type riser tube connections and 1/2" NPS Hose end Supply Connections.

Flanged Upper Showerhead is provided. Front Mounted Showerhead Wall Flange is solid brass, triple chrome-plated and includes a built-in 1.6 GPM Flow Restrictor. An Acorn Logan Wizard Showerhead is provided standard and is self-cleaning with an adjustable spray pattern from coarse stream to a fine mist. Optional Showerheads are also offered.

Handheld Shower Spray includes Pushbutton for On/Off control with non-positive shutoff, 60" long Stainless Steel Hose, Quick-Disconnect, Vacuum Breaker and Wall Hook [ADA, CBC-11B: 608.6]. Provided with 1.5 GPM Flow Control. **Fixed Head (-FH)** option in lieu of Handshower is available. Lower Fixed Head will be provided with standard Logan Wizard Showerhead or with any options selected for Upper Showerhead. For conformance with CBC select -FH-Y Universal Ball Joint on both Upper and Lower Showerheads for swivel angle adjustment [CBC 11B-608.6; Exception]. **Valve Control** may be selected with either Hot and Cold Mixing Valve or Single Temperature Metering Pushbutton

[CBC 11B-309.4].

- **-Type 8** Thermostatic/Pressure Balancing H&C Mixing Valve (recommended) is ASSE 1016 compliant to compensate for fluctuation in temperature and pressure. Includes patented ligature resistant Tri-Lever Handle (-LVR Lever Handle is optional).
- **-Type 6*** Air-Control Single Temp Pushbutton Metering Valve, non-hold open design. Timing from 5 to 60 seconds.

-Type 0* Electronic Single Temp Pushbutton Metering Valve styles provide an array of timing and programming options. Refer to individual Electronic Valve submittal sheets for specific data.

(*Note: Valve and piping differs from typical In-wall designs. Refer to Installation Instructions for complete details.)

Diverter Valve is provided to allow Upper Showerhead and Handheld Shower Spray to be operated independently [CBC 11B.608.6]. Includes patented ligature resistant ADA compliant Tri-Lever Handle (-LVR Lever Handle is optional). **"L" Shape Vinyl Padded Folding Seat and Two-wall Stainless Grab Bar** are provided. Refer to Acorn 1103 Series Seats and 1108 Series Grab Bars for technical details. Seat model is provided to match Valve Orientation (Specify). Wall mounting hardware is provided by others.

Page 1 S.500ADA

Revised: 02/02/24

Shower-Ware®: 500ADA Zenith Built-In Showers - ADA/CBC Compliant <

MODEL NUMBER AND OPTIONS SELECTION

MODEL N	SHOWERHEAD OPTIONS (One s			
SERIES (🗋 -A		Anchor Plate (Inclu	
5	Zenith	🛄 -В		Back Plate, Specify
SUPPLY (Must Specify)			
⊿ -3	Top or Bottom Supply	🛄 -ВА		Bent Arm
VALVE SE	-CSH -CSH-WSB		Conical Showerhea WaterSense 1.5 GI (Ligature Resistant	
☐ -6 ☐ -8	Air-Control, Single Temperature Metering T/P Temperature-Pressure Balancing Mixing Valve With Patented Ligature Resistant ADA Tri-Lever Handle (ASSE 1016 Compliant)	□ -F □ -MSH □ -P □ -Y		Flow Control 2.0 G Multi-Stream Show Penal Showerhead Universal Ball Joint
ELECTRO	NIC VALVE SELECTION	🗋 -YY		Lockable Universal
(Required	HANDHE	LD SH	IOWER OPTIONS	
🗋 -EVS1	ol® (Electronic) Single Temp Single Temp, Piezo Button	🗋 -FH	Fixed (Use	d Head at 48" MAX for ADA. Will receiv
Master-Trol [®] PLUS (Electronic)		🗋 -FH-Y		l Head at 48" MAX for CBC. Both head
🗋 -MTP1	Single Temp Single Temp, Piezo Button	🛄 -HL 🛄 -QD	Hi-Lo	b Dual Mounting Brack b Disconnect for Ha
Time-Trol		🛄 - P	SO Quick Disconn	
—	Single Temp	PRODUC	т орт	IONS
Programn	nable (Electronic) w/9VDC Plug-In Transformer Single Temp Programmable Piezo Button	-FSP		olic Folding Seat in Iless Steel Folding S
VALVE ORIENTATION (Must Specify)				Padded Folding Sea
	to coordinate Folding Seat model provided)	-LGB		Grab Bar
🗋 Left	🗋 Right	-LRD		Recessed Soap Dis
VALVE OF			LCOO	
-CI -LVR -PBH	Cycle Interrupt for Time-Trol Valves Lever Handle (Applies to -8 & Diverter Valve) Hemispherical Pushbutton (-6 Valve)			mal Shower Acces
🗋 -TF	Transformer, 120VAC to 24VAC (-MVC option)	Please v	visit <u>w</u>	vw.acorneng.com fo

SHOWERHEAD OPTIONS (One selection only.)

- uded with -CSH, -CSH-WSB)
- fy: Wall Thickness ____

	Wall Type		
🛄 -ВА	Bent Arm		
🖵 -CSH	Conical Showerhead (Ligature Resistant)		
-CSH-WSB	WaterSense 1.5 GPM Conical Showerhead		
	(Ligature Resistant)		
🖵 - F	Flow Control 2.0 GPM (Not Available in California)		
🗋 -MSH	Multi-Stream Showerhead		
🖵 -Р	Penal Showerhead		
🖵 -Y	Universal Ball Joint		
🗖 -YY	Lockable Universal Ball Joint		

s

- in Lieu of Handheld Shower eive any options selected above.)
- in Lieu of Handheld Shower ds require -Y Universal Ball Joint)
- rackets For Handheld Shower
- landheld Shower nect with Positive Shut-Off
- n Lieu of Padded Seat
- Seat in Lieu of Padded
- eat
- ish

essories are available at

om/bathroom-accessories

for most current specifications.

Layouts shown for reference only. Refer to applicable Accessibility Guidelines for complete dimensional data.								
NOTES:								
A A A A A A A A A A A A A A	riew 1. Flange 2. Handsl 3. Diverte 4. T/P Mit 5. Recess 6. Two-W 7. Contro 10" (254) . 38" (965) . 36" (914)	king Valve sed Soap Dish 'all Grab Bar I Area 9 Seat 36" Ref (914)	Top View 36" Ref (914) C SEAT SEE SIDE VIEW 4 4 4 4 4 4 4 4 4 4 4 4 4					
		-						
A WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov								
Important: Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acom assumes no responsibility for use of void or superseded data. © Copyright 2006 Acom Engineering Company								
Selection Summary		Approved for Manufacturing						
Model No. & Option		Company	Title					
Quantity			Date					
Page 2 S.500ADA Revised: 02/02/24								

Acorn Engineering Company • 15125 Proctor Avenue • P.O. Box 3527 • City of Industry, CA 91744-0527 U.S.A. Tel: (800) 488-8999 • (626) 336-4561 • www.acorneng.com • E-mail: info@acorneng.com