



Penal-Ware® 1665 Series

15" Econo Lavatory



1665-1-BPH-04

Fixture May Show Some Available Options

Please visit www.acorneng.com for most current specifications.

15" Econo Lavatory

Fixture is arranged to be installed on finished wall and serviced from an accessible pipe chase. Optional Wall Sleeve or Metal Template is recommended for all installations for required wall openings.

Cabinet is fabricated from 16 gage, type 304 stainless steel and is seamless welded construction. Cabinet interior is sound-deadened with fire-resistant material. There are no accessible voids or crevices where contraband can be concealed.

Lavatory Multi-Sided Bowl is 12-3/4" x 8-1/4" x 5" deep. Elbow waste outlet is 1-1/2" O.D. plain end and extends 3" minimum beyond the back of the wall.

Lavatory Valve is an pneumatically operated, pushbutton Air-Control valve using atmospheric air. Pushbutton is vandal-resistant and requires less than 5 pounds to activate valve. Valve is direct acting, non-metering type and is optionally available as metering with non-hold open feature. Metering valve timing is adjustable from 5 to 60 seconds. Valve includes a 0.5 GPM flow control and can be remotely located up to 10 feet from the operating pushbutton. Valve and Bubbler conforms with lead free requirements of NSF61, Section 9 and CHSC 116875.

Regularly Furnished items include a fast drain, integral raised soap ribs, and mounting hardware for walls up to 8" thick.

GUIDE SPECIFICATIONS

Provide and install Acorn Penal-Ware® 15" wide Econo Lavatory (specify model number and options). Fixture shall be fabricated from 16 gage, type 304 stainless steel. Construction shall be seamless welded. Counter top shall have raised soap ribs. Provide Air-Control pneumatically operated pushbutton valve. Valve and bubbler conform with lead free requirements for NSF61, Section 9 and CHSC 116875. Cabinet bottom shall be enclosed and have no accessible voids or crevices where contraband can be concealed. Cabinet interior is sound-deadened with fire-resistant material. Fixture shall withstand loadings of 1,500 pounds without permanent damage. Fixture shall be furnished with necessary fasteners for proper installation.



Penal-Ware®: 1665 15" Econo Lavatory

WALL THICKNESS AND TYPE (Must Specify)

Thickness: _____ Type: Concrete Block Steel

MODEL AND OPTIONS SELECTION:

BASE MODEL NUMBER

1665 15" Econo Lavatory

FIXTURE MOUNTING AND WASTE (Must Specify)

-1 Off-Floor, Wall Outlet

BUBBLER SELECTION (Must Specify)

-BPH Hemispherical Penal Bubbler

VALVE SELECTION (Must Specify)

Air-Control (Pneumatic)

- 03 Single Temp, Non-Metering
- 03-M Single Temp, Metering
- 04 Hot & Cold, Non-Metering
- 04-M Hot & Cold, Metering
- 04-MH Hot & Cold, Metering Hot Side Only

Valve By Others

-9 Punched for Valve by Others

VALVE OPTIONS

- BRS Brass Body Valve
- MA2 Manifolded, 2-Stack
- MA3 Manifolded, 3-Stack
- MA4 Manifolded, 4-Stack
- PBH Hemispherical Pushbutton

CABINET OPTIONS

- TB Toothbrush Holder Left Right
- TH Towel Hook Left Right


LAVATORY WASTE OPTIONS

- LW1 Thru-Wall Waste Extension with P-Trap

PRODUCT OPTIONS

- EG Enviro-Glaze, Specify Color: _____
- MT Metal Template (Only 1 Required Per Project)
- SW Wall Sleeve
- VAC AcornVac System


Please visit www.acorneng.com for most current specifications.



1665-1-BPH-04

NOTES:

1. -04 AIR-CONTROL VALVE
2. LAVY VALVE PUSHBUTTONS
3. -BPH HEMISPHERICAL PENAL BUBBLER
4. 1-1/2" OD PLAIN END WASTE OUTLET



FIXTURE INTENDED TO PROVIDE AN EXTENDED WASTE OUTLET BEYOND THE REAR OF UNIT EQUAL TO WALL THICKNESS PLUS 3" MINIMUM.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

<p>Important: Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. <small>Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acorn assumes no responsibility for use of void or superseded data. © Copyright 2009 Acorn Engineering Company</small></p>	
<p style="text-align: center;">Selection Summary</p> <p>Model No. & Option _____</p> <p>Quantity _____</p>	<p style="text-align: center;">Approved for Manufacturing</p> <p>Company _____ Title _____</p> <p>Signature _____ Date _____</p>