



### MODEL \*1823 MODEL \*1823-ECH



### MOUNTING DETAIL FOR 1/4' STUDS



REFERENCE DRAWINGS				
-SW Wall Sleeve	9925-292-001			
Mounting Hardware	9957-900-001			

## **INSTALLATION INSTRUCTIONS:**


- A-HAND TIGHTEN MOUNTING STUDS (1) INTO MOUNTING NUTS (2) ON BACK OF FIXTURE.
- B-POSITION FIXTURE 3 ON CELL SIDE, SLIDING STUDS 1 THROUGH SLEEVE OR WALL OPENINGS.
- C-PLACE WASHERS (4) OVER STUDS (1). THREAD NUTS (5) TO STUDS (1), & TIGHTEN. <u>DO NOT ALLOW</u> STUDS (1) TO TURN AND THREAD FURTHER INTO MOUNTING NUTS (2). <u>NOTE:</u> DO NOT EXCEED 6.5 FT/LBS MAXIMUM TORQUE ON 1/4" NUTS (5).

ACORN ENGINEERING COMPANY P.O. BOX 3527 INDUSTRY, CA. 91744 (626) 336-4561 FAX (626) 961-2200	REAR MOUNTED ACC	CESSORIES, CAT #1821, #1822,	*1823, *1825, *1827, *1829
	MANUFACTURE DATE	DATE ISSUED	DRAWING NUMBER
	DECEMBER 1971	4/16/97	
	TO PRESENT	DATE REVISED	9925-135-001
0			



### **BOTH VIEWS ARE FROM CELL SIDE**

SHADED AREAS ARE REQUIRED WALL OPENINGS



1) TYP.

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"

### 7"


### 7"

### 7"


### 7"


### 7"

### 7



CAT. \*1821 & 1822





CAT. #1825 & 1827

# **INSTALLATION INSTRUCTIONS:**


SLEEVES ARE INSTALLED IN FORMS USING NAIL HOLES

(1) PROVIDED OR GROUTED INTO BLOCK WALLS BECOMING A PERMANENT PART OF THE WALL.

NOTE: FOR POURED WALL CONSTRUCTION, TEMPORARY BRACING SHOULD BE INSTALLED WITHIN OPENING TO PREVENT DEFORMATION TO SLEEVE WHICH MAY OCCUR DURING POUR. DO NOT POUR CONCRETE DIRECTLY ON TOP OF WALL SLEEVE. THE OPENINGS ARE CAPPED; THESE CAPS ② MUST BE REMOVED FROM THE CHASE SIDE OF THE WALL SLEEVE BEFORE INSTALLING FIXTURE.

A-INSTALL SLEEVE AT DESIRED CELL SIDE HEIGHT WITH FLANGE (3) ON CHASE SIDE OF WALL.

B- WHEN SLEEVES ARE NOT AVAILABLE BLOCKOUT WITH DIMENSIONS SHOWN.



	ACORN ENGINEERING COMPANY P.O. BOX 3527 Industry, CA 91744 15125 Proctor Ave Industry, CA 91746 (626) 336-4561 FAX (626) 961-2200	WALL SLEEVES (CAT. *1810,	1812, 1821, 1822, 1823	& 1825
	. ,	MANUFACTURE DATE	DATE ISSUED	DRAWING NUMBER
		DECEMBER 1971	03/01/90	
/16		TO PRESENT	DATE REVISED 10/30/12	9925-292-001