

## Wash-Ware® 3351 Series

Retro-Pak - Replacement



Fixture May Show Some Available Options

Please visit **www.acorneng.com** for most current specifications.

## **Retro-Pak Replacement**

**The Acorn Retro-Pak** has been designed to completely replace the operating mechanism on Bradley HC model Washfountains.

**BRADLEY MODELS:** CHC 554, CHC 536, KHC 5541\*

**The Acorn Retro-Pak** replaces the sprayhead, soap dispensing system and valve assembly. The Retro-Pak sprayhead and stanchion assembly is fabricated entirely of type 304 stainless steel with a satin finish. Acorn's sprayhead is designed to contain the pushbuttons, individual spray nozzles and optional soap system. The sprayhead assembly is mounted to the existing bowl, using tie rods and supporting castings. Gasket for applicable bowl material is included.

**The Valve Assembly,** including the single handle pressure balancing mixing valve and the individual, non-hold open metering valves are arranged to be located within the existing pedestal. A mounting bracket is included to accommodate wall or floor mounting.

**Valves** are Air-Control pneumatically operated, pushbutton type using atmospheric air. Pushbutton is vandal-resistant and requires less than 5 pounds to activate valve. Valve is metering type with non-hold open feature. Timing is adjustable from 5 to 60 seconds.

**Regularly furnished** items include sprayhead, sprayhead stanchion, upper and lower support castings, tie rods, gasket, pressure balancing mixing valve, strainer checks, and Air-Control metering valves (one per washing station).

## **GUIDE SPECIFICATION**

Provide and install Acorn Retro-Pak (specify model number and options) with individual Air-Control non-hold open metering valves and spray nozzles. Sprayhead and stanchion to be type 304 stainless steel with a satin finish.

\* These models are registered trademarks of Bradley Corporation.

Page 1 W.3351 Revised: 01/04/22

## W

Retro-Pak (For Replacing Bradley

Sensor Operated, Battery Powered

Wash-Ware®: 3351 Retro-Pak - Replacement								
REPLACEMENT WASHFOUNTAIN DESCRIPTION (Must Specify)			-DV	OPTIONS (Must Specify) Liquid / Lotion Soap Dispenser				
Configuration	s: 🔲 Semi-Circular	Corner	☐ -PDM ☐ -SC	Metering Liquid Soap Dispenser Supply Vent Cover Ceiling				
Number of Users: 4 3		<u> </u>	_	Height:				
Supplies:	☐ From Above	From Below	☐ -ST	Single Temperature Supply				
Vent:	Centrally Rising	g 🔲 Off Drain						
MODEL NUMBER AND OPTIONS SELECTION								

Please visit www.acorneng.com for most current specifications.

HC Models)

Hand Operation

Sensor Operation

(Batteries Not Included)


**BASE MODEL NUMBER** 

**OPERATION (Must Specify)** 

**☑** -3351

Ū-so

-SO-BAT



**SEMI-CIRCULAR** FRONT VIEW WITH ACORN RETRO-PAK

34" (864)Reference **SEMI-CIRCULAR** 

SIDE VIEW WITH ACORN RETRO-PAK

MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

MODEL# 3351-H

NOTES:

1. Valve Pushbuttons.

2. Spray Nozzles.

Series 3. Valve Assembly.

	<del>-</del>							
Important: Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions.  Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acom assumes no responsibility for use of void or superseded data. © Copyright 2004 Acom Engineering Company								
Selection Summary			Approved for Manufacturing					
	Model No. & Option		Company	Title				
	Quantity		Signature	Date				

Page 2 W.3351 Revised: 01/04/22